

CANON EOS C300 Power Solutions

The QRC-CA940 provides the convenience of powering the Canon EOS C300 via a DC connector, as well as having 3 PowerTap outputs for powering accessories such as monitors and recorders to help simplify on-set battery management and reduce down time when changing batteries.



Canon EOS C300



AJA Ki Pro Mini



QRC-CA940



DIONIC® 90



DIONIC® HC




DIONIC® HCX



Tandem® 70
70 Watt AC
Power Supply
and Charger



AJA Ki Pro Mini



MATRIX Cheese Plate
w/15 mm or 19 mm
Rod Clamp Kit



QRC-CA940

ACCESSORIES

PowerTap® XLR-9

9" PowerTap cable to 4-pin XLR

PowerTap® XLR-20

20" PowerTap cable to 4-pin XLR

APPROXIMATE RUN-TIMES

	Canon EOS C300	Canon EOS C300 w/AJA Ki Pro Mini
DIONIC 90	8 hrs	3 hrs
DIONIC HC	7-1/2 hrs	3 hrs
DIONIC HCX	10-1/3 hrs	4 hrs



One World. One Smart Choice.™
www.antonbauer.com

Anton/Bauer Inc., 14 Progress Drive, Shelton, Connecticut 06484 USA • (203) 929-1100 • Fax (203) 925-4988
Anton/Bauer Europe, B.V. Eurode Business Center, Eurode-Park 1-2, 6461 KB Kerkrade, The Netherlands • (+31) 45 5639220 • Fax (+31) 45 5639222
Singapore Office - Anton/Bauer, 6 New Industrial Road, # 02-02 Hoe Huat Ind. Bld., Singapore 536199 • (+65) 62975784 • Fax (+65) 62825235